

Technical Information

Product Features			
Rated Wattage	13W	15W	
Replaces	60W incandescent light bulbs	35W & 50W Halogen (in white/chrome)	Adaptor plate for 15W MDL (in white/chrome)
Fitting specification	Bayonet and Edison screw	Quick Release	
Tube specification	T2	T2	
Length	122mm	100mm	
Diameter	44mm	88mm (outer) 50mm (inner)	150mm
Suitable for residential downlights?	Yes	Yes	
Suitable for high on/off switching areas?	Yes	Yes	
Suitable for dimmers?	No	No	
Light output & Efficacy	650 Lumens 56 lm/W	950 Lumens 60 lm/W	
Light colour	2700K, 5000K & 6500K	2700K, 5000K & 6500K	
Average service life	8,000h	10,000h (bulb) 30,000h (ballast)	
Power Factor	>0.9	>0.9	
Total Harmonic Distortion	<30% THD	<30%THD	
Mercury (Hg) content	1.5mg	1.5mg	
Recycled packaging?	Yes	Yes	Yes
Each ecobulb product tested before shipping?	Yes	Yes	
Guarantee	2 Years	2 Years	

ecoBright® energy solutions ABN 73 121 912 356
Office 15, 207-211A Buckley Street Essendon VIC 3040 Australia
T +61 3 9331 0027 **F** +61 3 9331 0028
E info@ecobright.com.au **W** www.ecobright.com.au

ecoBright® energy solutions Limited GST 100 126 877
Unit 16, 6 Airborne Road Albany North Shore City 0632 New Zealand
T +64 9 415 7345 **F** +64 9 415 7346
E info@ecobright.co.nz **W** www.ecobright.co.nz

ecoBright® energy solutions is a trade mark of ecoBright® Pty Ltd
© Copyright - ecoBright® Pty Ltd v.06/10

The information in this technical sheet is for ecoBright® customers. ecoBright® shall not be held liable for any costs, losses or damages howsoever caused as a result of reliance on the information it contains. Specific product types may not be available in all regions, for more information on ecoBright® products and applications please contact staff at your local office.

